

Air Compressor Needs Quick Fact Sheet

• The 8 Shooter Filler & Crowner only uses up to 7 cfm

- The AutoLoader uses less than 1 cfm
- The Spin Labeler uses less than 2 cfm
 - No particular brand required
- Please note, The following specification may not supply enough compressed air for simultaneous bottling/keg washing operations

These needs would be met for a brewery through the use of an air compressor with the following specs:

- 7.5hp
- 80 gallon
- Splash Lubricated
 - 24.3 CFM

Additionally, for trouble-free operation, the 8S & AL & SL require an Air Dyer with the following specs:

- 25 cfm
- 7.5 hp maximum
 - 250 psi

Quick Fact Sheet

GRAINGER http://www.grainger.com/ ...Or your Local Suppliers

Back to Product Family

///



How can we improve our Product images?

7-1/2 HP, 80 gal. Horizontal Splash Lubricated Tank Mounted Electric Air Compressor, CFM: 24.3 SPEEDAIRE

Price • \$3,620.00 / each	Deliver 1 1 or	Availability for Qty Shipping Expected to arrive T Ship to: 68501 (Cha	
会会会会会 Be the first Item # 35WC52		UNSPSC # 40151	501

Country of Origin USA | Country of Origin Is subject to change.

Note: Product availability is real-time updated and adjusted continuously. The product will be reserved for you when you complete your order. More

Technical Specs

Compare

item	Electric Air Compressor	dBA @ 3 Feet	85
Compressor Type	Tank Mounted	Pump RPM	1020
Number of Stages	2	Pump Oll Capacity	2 qt.
Lubrication Type	Splash Lubricated	On Pressure Switch Setting	145
HP	7-1/2	Off Pressure Switch	175
Max. Pressure	175 psi	Setting	
		Cylinder Material	Cast iron
Free Air CFM @ Max. Pressure	24.3	Finish	Powder Coated
Voltage	208-230/460	Enclosure	Open Drip Proof
Phase	3	Control	Pressure Switch
Amps	19.8-17.9/9	Motor Type	Open Dripproof
Hz	60	Overall Length	ez
Tank Size	80 gal.	Overall Width	21"
Tank Type	Horizontal	Overall Height	46"
Compressor Package Type	Fully Packaged	Standards	ASME, CSA
ASME Tank	Yes	Includes	Air Cooled Aftercooler, Motor Starter, Electronic Drain Valve, Oli Sight Glass,
(F)NPT Outlet	3/4-		Pressure Gauge, Pressure Safety Valve, Tri-voltage Motor



GRAINGER http://www.grainger.com/ ...Or your Local Suppliers



ltem	Compressed Air Dryer	Max. Inlet Temp.	120 Degrees F
ISO Class	6	Max. Amblent Temp.	113 Degrees F
CFM	25	Refrigeration Compressor (HP)	1/4
Dew Point	46 Degrees F	Finish	Powder Coated
Max. Air Compressor HP	7.5	Bracket Kit	No
Max. Pressure	250 psi	Overall Height	22-
Pipe Size	3/4" NPT	Overall Width	15"
Voltage	115VAC	Overall Depth	16"
Phase	1	Features	On/Off Switch
Full Load Amps	6.00	Includes	3 Micron Solid Particle Filter