CREST ULTRASONICS F-300 SERIES Open Top Solvent Cleaning Systems

...designed to safely employ all of todays non-flammable and EPA approved solvents

The F-300 series is an economical solution to solvent precision cleaning applications. A typical process includes immersion in the latest ultrasonic technology with ceramically enhanced transducers that produces unrivalled cleaning with HFC, HFE, NPB, and HCFC solvents.

FEATURES

• Solvent immersion tank with patented Crest 40, 58 132, or 192kHz ultrasonics

- Closed-Loop Hot Water Heating of Solvent and Vapor
- Dual compressor refrigeration
- PLC control with automation capability
- 120% freeboard ratio to limit solvent comsumption
- True Superheat[™] For Rapid Part Drying
- Recirculation with cartridge filtration

- Two gravity water separators with molecular sieve capability
- Compact footprint for easy integration in production flow
- Manual downtime cover
- Stainless steel condenser and chiller coils to avoid corrosion
- Stainless steel process tanks with bright annealed finish
- Solvent cool down mode to minimize solvent loss



F-300 with optional Automated Transport System

F-300 Series

Open Top Solvent Cleaning Systems

Model	Tank Size	Distillation Rate	Heat	Load Capacity	Solvent _{Capacity}	Electrical Requirements	Cooling Water Requirements	Ultrasonics
	Inches	Gal/Hr	kW	Lbs/Hr	Gal			
F-300- 1812	18 x 12 x 12	13	7.5	600	37	208V - 3 PH - 60A	6 GPM @ 85 °F	40, 58, 132, 192 kHz - 2000W
F-300- 2016	20 x 16 x 16	25	15	900	70	480V - 3 PH - 70A	12 GPM @ 85 °F	40, 58, 132, 192 kHz - 3000W
F-300- 2420	24 x 20 x 18	37	24	1230	100	480V - 3 PH - 100A	15 GPM @ 85 °F	40, 58, 132, 192 kHz - 4000W

The F-300 series is ideal for removing residues like films, fingerprints, greases, mold releases, oils, etc. Applications can be found in most industrial domains.



Safety

- Refrigeration temperature monitoring
- Boiling tank over temperature signal with solvent replacement warning
- Extended freeboard volume
- Boiling tank low level control
- · Vapor level control with reset

Options

- · Desiccant water removal
- Baskets
- Parallel Automated transport system
- Powered cover
- Upper enclosure
- Chillers available

ADVANTAGES

- Wash, rinse, and dry with a spot free finish in one compact unit
- Smaller footprint and faster cycle times than aqueous systems
- No water consumption or wastewater treatment required
- No exhaust required



F-300 Series System Layout



PO Box 7266 Scotch Road Trenton NJ 08628 Phone: 609-883-4000 Fax: 609-883-6452 sales@crest-ultrasonics.com www.crest-ultrasonics.com