

SYNCROLITE™

WORLD LEADER IN ARCHITECTURAL & THEATRICAL AUTOMATED XENON LIGHTING SYSTEMS



MX3000

- Lamp: 2000W Xenon
- Reflector: 10" custom high performance reflector- 99% reflective
- Control: Standard 14-channel DMX
- Operation: Opto-isolated electronics, servo motor operation
- Pan: 540° variable speed
- Tilt: 250° variable speed
- Beam: Variable collimated spot to 20° flood
- Scroller: Triple variable speed gel scrollers for DichroFilm™ OmniColor™ color mixing system, gobo effects, and VFL™ lenses- 10, 20 & 30 degree.
- Intensity: High-speed Venetian blind douser/ strobe
- Mounting options: Flyable in all planes or ground mount
- Ext. Construction: Weatherproof powdercoated aluminum
- Weight: Lamphead 122 lbs
- Dimensions: 23"W x 27.5"D x 44.5"H
- Ballast: SBE 3X2-S 3-way ballast pack
- Power Requirement: US: 8A/phase 3-phase 120-208V 5-wire
Europe: 5A/phase 3-phase 220-380V
Asia: 5A/phase 3-phase 240-400V 5-wire

UL/ETL/CE Listed, Listing Ref: #3031978-001