



US008959874B2

(12) **United States Patent**  
**Wasterval**

(10) **Patent No.:** **US 8,959,874 B2**

(45) **Date of Patent:** **Feb. 24, 2015**

(54) **PORTABLE DRILLING RIG APPARATUS AND ASSEMBLY METHOD**

(56) **References Cited**

- (71) Applicant: **Philip Wasterval**, Edwards, CO (US)
- (72) Inventor: **Philip Wasterval**, Edwards, CO (US)
- (73) Assignee: **International Drilling Equipment Company, LLC**, Spring, TX (US)
- (\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

U.S. PATENT DOCUMENTS

867,536	A *	10/1907	Rochford	175/89
2,268,796	A	1/1942	Brauer	
2,565,777	A	8/1951	Moon	
2,594,847	A *	4/1952	Bates et al.	173/37
2,689,549	A *	9/1954	Hayman	91/169
2,829,741	A	4/1958	Selberg et al.	
2,852,111	A	9/1958	Fuller et al.	
2,857,993	A *	10/1958	Terrell	52/120
2,920,725	A	1/1960	Emmons	
2,993,570	A *	7/1961	Bender	52/118
3,016,992	A *	1/1962	Wilson	52/115
3,071,213	A *	1/1963	Bender	52/117
3,181,658	A *	5/1965	Bender	52/116
3,228,151	A *	1/1966	Woolslayer et al.	52/64
3,262,237	A *	7/1966	Jenkins et al.	52/116
3,271,915	A *	9/1966	Woolslayer et al.	52/120
3,295,270	A *	1/1967	Woolslayer et al.	52/117

(21) Appl. No.: **13/899,293**

(22) Filed: **May 21, 2013**

(65) **Prior Publication Data**

US 2013/0318909 A1 Dec. 5, 2013

**Related U.S. Application Data**

(62) Division of application No. 12/568,489, filed on Sep. 28, 2009.

(51) **Int. Cl.**  
**E21B 7/02** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **E21B 7/023** (2013.01); **E21B 7/021** (2013.01)  
USPC ..... **52/745.18**; 52/117; 52/118; 52/119; 52/146; 52/651.05

(58) **Field of Classification Search**  
USPC ..... 52/116-119, 146, 632, 651.01, 651.05, 52/651.07, 745.19, 745.2, 745.17, 745.18; 173/28, 42, 44, 190, 193; 166/379; 175/162, 203

See application file for complete search history.

(Continued)

FOREIGN PATENT DOCUMENTS

JP 06235263 A \* 8/1994 ..... E04G 21/16

OTHER PUBLICATIONS

Office Action issued in related U.S. Appl. No. 12/568,489 mailed Jul. 29, 2014 (13 pages).

*Primary Examiner* — Robert Canfield


*Assistant Examiner* — Charissa Ahmad

(74) *Attorney, Agent, or Firm* — Osha Liang LLP

(57) **ABSTRACT**

A portable drilling rig apparatus includes a rig floor having a pedestal structure thereon, the pedestal structure comprising a lower pivot point and a lower attachment point and wherein the pedestal structure is configured to be rotated to a vertical position about the lower pivot point. The drilling rig further includes a mast structure having a mast pivot point at a lower end of the mast structure wherein the mast pivot point is configured to be pinned to an upper pivot point of the pedestal structure.

**10 Claims, 11 Drawing Sheets**




(56)

References Cited

U.S. PATENT DOCUMENTS

3,403,485	A *	10/1968	Cernosek	52/121	4,831,795	A *	5/1989	Sorokan	52/120
3,483,933	A *	12/1969	Dyer et al.	173/39	5,450,695	A	9/1995	Desai	
3,719,238	A *	3/1973	Campbell et al.	173/147	6,523,319	B2 *	2/2003	Bockhorn et al.	52/651.01
3,747,695	A *	7/1973	Branham	173/151	6,594,960	B2 *	7/2003	Brittain et al.	52/117
3,803,780	A *	4/1974	Donnally	52/116	6,634,436	B1 *	10/2003	Desai	173/1
3,807,109	A *	4/1974	Jenkins et al.	52/120	6,848,515	B2 *	2/2005	Orr et al.	173/1
3,817,397	A	6/1974	Wellman		6,994,171	B2 *	2/2006	Orr et al.	173/28
3,922,825	A *	12/1975	Eddy et al.	52/116	7,306,055	B2 *	12/2007	Barnes	175/57
3,942,593	A *	3/1976	Reeve et al.	173/186	7,308,953	B2 *	12/2007	Barnes	175/203
4,024,924	A *	5/1977	Houck	173/151	7,413,393	B1 *	8/2008	Barnes	414/373
4,078,617	A *	3/1978	Cherrington	173/1	7,765,749	B2 *	8/2010	Palidis	52/112
4,135,340	A *	1/1979	Cox et al.	52/115	7,828,087	B2 *	11/2010	Vora	175/220
4,221,088	A *	9/1980	Patterson	52/116	7,931,076	B2 *	4/2011	Ditta et al.	166/75.11
4,375,241	A *	3/1983	Gallon	173/151	8,468,753	B2 *	6/2013	Donnally et al.	52/117
4,489,526	A *	12/1984	Cummins	52/125.6	8,572,926	B2	11/2013	Vangsy et al.	
4,578,911	A *	4/1986	Hashimoto	52/120	2003/0051915	A1 *	3/2003	Brittain et al.	175/52
4,598,509	A *	7/1986	Woolslayer et al.	52/118	2003/0172599	A1 *	9/2003	Frink	52/116
4,616,454	A *	10/1986	Ballachey et al.	52/115	2004/0211598	A1 *	10/2004	Palidis	175/162
4,759,414	A *	7/1988	Willis	175/170	2005/0194189	A1 *	9/2005	Barnes	175/122
					2009/0000218	A1 *	1/2009	Lee et al.	52/123.1
					2009/0218144	A1 *	9/2009	Donnally et al.	175/162
					2009/0321135	A1 *	12/2009	Vora	175/57

\* cited by examiner



**FIG. 1**  
**(Prior Art)**








FIG. 2

















FIG. 7










FIG. 11

## PORTABLE DRILLING RIG APPARATUS AND ASSEMBLY METHOD

### CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is a divisional application of and, thereby, claims benefit under 35 U.S.C. §120 to U.S. patent application Ser. No. 12/568,489 filed on Sep. 28, 2009, titled, "PORTABLE DRILLING RIG APPARATUS AND ASSEMBLY METHOD." The contents of the priority application are incorporated by reference in its entirety.

### BACKGROUND

#### 1. Field of the Disclosure

Embodiments disclosed herein relate generally to drilling rigs. In particular, embodiments disclosed herein relate to portable drilling rig apparatuses and related methods of assembly.

#### 2. Background Art

A drilling rig is used to drill a wellbore in a formation. Drilling rigs may be large structures that house equipment used to drill water wells, oil wells, or natural gas extraction wells. Drilling rigs sample sub-surface mineral deposits, test rock, soil and groundwater physical properties, and may also be used to install sub-surface fabrications, such as underground utilities, instrumentation, tunnels or wells. Drilling rigs may be mobile equipment mounted on trucks, tracks, or trailers, or more permanent land or marine-based structures (such as oil platforms). The term "rig," therefore, generally refers to a complex of equipment that is used to penetrate the surface of the earth's crust.

Referring to FIG. 1, a conventional drilling rig **30** is shown. Drilling rig **30** includes a derrick **14**, which provides a support structure for a majority of the equipment used to raise and lower a drillstring **25** into and out of a wellbore. The drillstring **25** may be an assembled collection of drillpipe, drill collars, or any other assortment of tools, connected together and run into the wellbore to facilitate the drilling of a well (drillpipe **16** is shown in joints prior to being connected together). The drillstring **25** may be raised and lower into and out of the wellbore by the draw-works **7**, which includes a spool powered by a motor or other power source **5**. A drill line **12**, which may be a thick, stranded metal cable, is run from the draw-works **7** over a crown block **13** and down through a travelling block **11**. Typically, the crown block **13** remains stationary while the travelling block **11** moves vertically with the drillstring **25**. The combination of the crown block **13** and the travelling block **11** provides a significant mechanical advantage for lifting the drillstring **25**. Further, a swivel **18** may be attached to the travelling block **11** to allow rotation of the drillstring **25** without twisting the travelling block **11**.

The drilling rig **30** further includes a rotary table **20** mounted in a rig floor **21**, which is used to rotate the drillstring **25** along with a kelly drive **19**. Kelly drive **19**, attached at an upper end to the swivel **18** and at a lower end to the drillstring **25**, is inserted through the rotary table **20** to rotate the drillstring **25** (drillstring rotation shown by arrow "R"). Kelly drive **19** may be square, hexagonal, or any other polygonal-shaped tubing and is able to move freely vertically while the rotary table **20** rotates it. Alternatively, drilling rig **30** may include a top drive (not shown) in place of kelly drive **19** and rotary table **20**. Additionally, blowout preventers ("BOPs") may be located below the rig floor **21** and installed atop a wellhead **27** to prevent fluids and gases from escaping from

the wellbore. An annular BOP **23** and one or more ram BOPs **24** are shown and are commonly understood in the art.

During drilling operations, drilling fluid may be circulated through the system to carry cuttings away from the bottom of the wellbore as drilling progresses. Drilling fluid may be stored in mud tanks **1** before being drawn through suction line **3** by mud pumps **4**. Drilling fluid (drilling fluid route is indicated by arrows "F") is then pumped from mud pumps **4** through a hose **6**, up a stand pipe **8**, through a flexible hose **9**, and down into the wellbore. Drilling fluid returning from the wellbore is routed through a flow line **28** to shakers **2**, which are used to separate drill cuttings from the drilling fluid before it is pumped back down the wellbore.

Drilling rigs may add considerable cost to the overall costs of extracting oil or natural gas from underground reservoirs. This may be due to large equipment needed to erect certain drilling rigs or the difficulty of erecting certain drilling rigs in remote locations where it may be more costly to transport the drilling rig. Also, certain oil and natural gas wells may have a relatively limited well life, i.e., the well has only a limited amount of gas or oil capable of being extracted. Because of the reduced production, to maintain profitable margins from drilling and producing such a well, a less expensive drilling rig would be desirable. Thus, there exists a need for an economical drilling rig capable of being transported to remote and difficult to reach locations.

### SUMMARY OF THE DISCLOSURE

In one aspect, embodiments disclosed herein relate to a portable drilling rig apparatus including a rig floor having a pedestal structure thereon, the pedestal structure comprising a lower pivot point and a lower attachment point and wherein the pedestal structure is configured to be rotated to a vertical position about the lower pivot point. The drilling rig further includes a mast structure having a mast pivot point at a lower end of the mast structure wherein the mast pivot point is configured to be pinned to an upper pivot point of the pedestal structure.

In other aspects, embodiments disclosed herein relate to a method to assemble a portable drilling rig, the method including providing a pedestal structure on a rig floor, the pedestal structure comprising a lower pivot point, a lower attachment point, and an upper pivot point. The method further includes aligning a mast structure and the pedestal structure, pinning a mast pivot point located at a lower end of the mast structure to the upper pivot point of the pedestal structure, and pivoting the pedestal structure from a substantially horizontal position to a vertical position. Further, the method includes moving the mast structure in a horizontal direction toward a center of the rig floor, securing the lower attachment point of the pedestal structure to a corresponding attachment point on the rig floor, erecting the mast structure from a substantially horizontal position to a vertical position about a pivot point between the mast structure and the pedestal structure, and securing the mast structure in a vertical position.

In other aspects, embodiments disclosed herein relate to a method to assemble a portable drilling rig, the method including attaching a mast structure to a pedestal structure on a rig floor and pivoting the pedestal structure from a horizontal position to a vertical position about a lower pivot point and securing the pedestal structure to the rig floor.

In other aspects, embodiments disclosed herein relate to an apparatus to restrict axial movement between an inner mast section and an outer mast section, the apparatus including a latch mechanism pivotably connected to the inner mast section wherein the latch mechanism is configured to move

between a collapsed position and an extended position. The apparatus further includes a first cutout formed in an outer surface of the inner mast section wherein the latch mechanism sits flush with the outer surface of the inner mast section when the latch mechanism is in the collapsed position, and a second cutout formed in an inner surface of the outer mast section, wherein the latch mechanism is configured to be extended radially and engage the second cutout in the inner surface of the outer mast section.

Other aspects and advantages of the invention will be apparent from the following description and the appended claims.

#### BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is a cross-sectional schematic view of a conventional drilling rig.

FIG. 2 is a perspective view of a portable drilling rig prior to assembly in accordance with embodiments of the present disclosure.

FIG. 3 is a perspective view of the portable drilling rig at a first intermediate assembly stage in accordance with embodiments of the present disclosure.

FIG. 4 is a perspective view of the portable drilling rig at a second intermediate assembly stage in accordance with embodiments of the present disclosure.

FIGS. 5-6 are perspective views of the portable drilling rig at third and fourth intermediate assembly stages in accordance with embodiments of the present disclosure.

FIGS. 7-8 are perspective views of the portable drilling rig at fifth and sixth intermediate assembly stages in accordance with embodiments of the present disclosure.

FIG. 9-10 are perspective views of the portable drilling rig at seventh or eighth intermediate assembly stages in accordance with embodiments of the present disclosure.

FIG. 11 is a cross-sectional view of a latch to secure telescoping mast sections of the portable drilling rig in accordance with embodiments of the present disclosure.

#### DETAILED DESCRIPTION

In one aspect, embodiments disclosed herein relate to portable drilling rig apparatuses and related methods of assembling the portable drilling rig.

Referring to FIG. 2, a perspective view of a portable drilling rig 100 prior to assembly is shown in accordance with embodiments of the present disclosure. The drilling rig 100 includes a base assembly 120 and a mast structure 110 configured to be installed on the base assembly 120. The base assembly 120 includes a collapsible rig floor 122, which will be described later.

Drilling rig 100 may further include a pedestal structure 130 that may be mounted on rig floor 122 and configured to link mast structure 110 and rig floor 122, as well as aid with assembly of the drilling rig 100. Pedestal structure 130 may include an upper attachment point 132 configured to be pinned to a mast pivot point 112 during assembly. Pedestal structure 130 may also include a lower pivot point 134, which is pinned to rig floor 122, about which pedestal structure 130 may pivot and a lower attachment point 136 where pedestal structure is pinned to rig floor 112 after being positioned in a vertical position, as explained later. Initially, as shown in FIG. 2, pedestal structure 130 may be laid over in a substantially horizontal position, in which lower attachment point 136 is unpinned, thereby allowing pedestal structure 130 to freely pivot about lower pivot point 134.

Referring now to FIG. 3, a perspective view of portable drilling rig 100 at a first intermediate assembly stage is shown in accordance with embodiments of the present disclosure. To begin assembly, mast pivot point 112 of mast structure is aligned with upper pivot points 132 of pedestal structure and pinned together. Hydraulic cylinders 140, attached to mast structure 110 and a first attachment point 142 on base assembly 120, may be used to properly align mast pivot point 112 and upper pivot point 132 prior to pinning them together. Once mast pivot point 112 and upper pivot point 132 are pinned together, mast structure 110 is moved horizontally in direction "H" toward a center 123 of rig floor 112. Again, hydraulic cylinders 140 may be used to move mast structure 110 horizontally. Because mast structure 110 is pinned at mast pivot point 112 to upper pivot point 132 of pedestal structure, movement of mast structure 110 in direction H may pivot pedestal structure upward about lower pivot point 134.

Now referring to FIG. 4, a perspective view of portable drilling rig 100 at a second intermediate assembly stage is shown in accordance with embodiments of the present disclosure. Hydraulic cylinders 140 continue to move mast structure 110 horizontally, and pedestal structure 130 continues to rotate about lower pivot point 134 until lower attachment points 136 of pedestal structure 130 are aligned with corresponding rig floor attachment points 124 of rig floor 122. Once aligned, lower attachment points 136 and rig floor attachment points 124 may be pinned, thereby securing pedestal structure 130 to rig floor 112 and preventing pedestal structure 130 from pivoting about lower pivot points 134 any further.

Referring now to FIGS. 5 and 6, perspective views of portable drilling rig 100 at third and fourth intermediate assembly stages are shown in accordance with embodiments of the present disclosure. Hydraulic cylinders 140 previously used to move mast structure 110 horizontally may be moved from first attachment point 142 (FIG. 4) and reattached to a second attachment point 144, which provides the hydraulic cylinders 140 with a new range of motion used to erect mast structure 110. As shown, hydraulic cylinders 140 may be extended to erect mast structure 110 as mast structure 110 pivots about the attachment between upper pivot point 132 and mast pivot point 112.

FIG. 6 illustrates mast structure 110 after it has been raised to a final vertical position. As shown, hydraulic cylinders 140 may be fully extended to erect mast structure 110. To secure mast structure to rig floor 122, a mast leg 114, which connects to a point on mast structure 110 and rig floor 112, may be fully extended and fastened. Once installed, hydraulic cylinders 140 may be retracted, as they are no longer needed.

Referring now to FIGS. 7 and 8, perspective views of portable drilling rig 100 at fifth and sixth intermediate assembly stages are shown in accordance with embodiments of the present disclosure. After mast structure 110 is fully erected and secured, rig floor 122 may be elevated to a specified height. As previously described, this specified height is often driven by requirements for the height of a crown block (13 in FIG. 1) or blowout prevention equipment (23, 24 in FIG. 1) installed below rig floor 122, which will be understood by those skilled in the art. In certain embodiments, a hydraulic system 126, mounted at a lower end to skids 128 and an upper end to rig floor 112, may be used to elevate rig floor 122. Those skilled in the art will understand that pneumatic and mechanical systems may also be used.

FIGS. 9 and 10 are perspective views of portable drilling rig 100 during seventh and eighth intermediate assembly stages in accordance with embodiments of the present disclosure, at which point mast structure 110 is extended to a final

5

(drilling) height. As shown, mast structure **110** may be configured as a telescoping structure including multiple mast sections **111**, **112**, and **113**, with each mast section having a slightly smaller cross-sectional area than the mast section below it. In this way, multiple mast sections are able to fit within the mast section below it, thus allowing the mast structure **110** to be collapsed to a shorter length for easier transportation and handling during assembly. The mast sections may be raised using hydraulics, pneumatics, mechanical devices, or other methods known to those skilled in the art.

Referring now to FIG. **11**, a cross-sectional view of a latch **200** used to lock and restrict movement between the extended mast sections of mast structure is shown in accordance with embodiments of the present disclosure. Latch **200** may be installed on a smaller inner mast section **210**, or a mast section that fits inside a slightly larger outer mast section **220**. Inner mast section **210** has a cavity or cutout **212** formed in an outer surface of inner mast section **210** in which latch **200** may be positioned to sit flush with an outer profile of inner mast section **210** (so that inner mast section **210** is free to slide up and down within outer mast section **220** when latch **200** is collapsed). Similarly, outer mast section **220** has a corresponding cutout **222** formed in an inner surface of outer mast section **220**, into which latch **200** may extend to secure the two mast sections relative to each other. Latch **200** is attached to inner mast section **210** at an attachment point **216** about which latch **200** is able to pivot and move from a collapsed position to an extended position (shown). Further, a spring **214** may be provided to bias latch **200** into an extended position and a cable **218** (or other device) may be provided to operate latch **200**.

As such, when mast sections are extended (e.g., as shown in FIGS. **9** and **10**), latch **200** may be aligned with cavity **222** formed in an inner surface of outer mast section **220**, at which point latch **200** may be extended radially outward to engage cavity **222**. When engaged, latch **200** contacts a ledge **213** of inner section **210** and ledge **223** of outer section **220**, so that load forces (represented by "F") may be transmitted from inner section **210**, through latch **200**, and into outer section **220**.

Advantageously, embodiments of the present disclosure for a highly mobile and economical drilling rig capable of reaching remote well locations. The unique pedestal structure eliminates a need for large cranes or other lifting equipment typically required to erect a mast structure, making the drilling rig easily portable to various locations. Additionally, because less equipment is required for assembly, initial assembly costs for setting up the drilling rig may be reduced, which in turn may increase profit margins from smaller or limited production wells.

While the present disclosure has been described with respect to a limited number of embodiments, those skilled in the art, having benefit of this disclosure, will appreciate that other embodiments may be devised which do not depart from the scope of the disclosure as described herein. Accordingly, the scope of the disclosure should be limited only by the attached claims.

What is claimed is:

**1.** A method to assemble a portable drilling rig, the method comprising:

- providing a pedestal structure on a rig floor;
- the pedestal structure comprising a lower pivot point, a lower attachment point, and an upper pivot point;
- aligning a mast structure and the pedestal structure;

6

pinning a mast pivot point located at a lower end of the mast structure to the upper pivot point of the pedestal structure;

5 pivoting the pedestal structure from a substantially horizontal position to a vertical position;

moving the mast structure in a horizontal direction toward a center of the rig floor;

securing the lower attachment point of the pedestal structure to a corresponding attachment point on the rig floor;

erecting the mast structure from a substantially horizontal position to a vertical position about a pivot point between the mast structure and the pedestal structure; and

securing the mast structure in a vertical position.

**2.** The method of claim **1**, further comprising elevating the rig floor to a specified height.

**3.** The method of claim **1**, further comprising extending a mast leg from the mast structure to the rig floor to secure the mast structure in a vertical position.

**4.** The method of claim **1**, wherein erecting the mast structure comprises extending at least one hydraulic cylinder attached to the mast structure and the rig floor.

**5.** The method of claim **4**, further comprising extending multiple telescoping mast sections of the mast structure to a final height.

**6.** The method of claim **5**, further comprising latching the multiple telescoping mast sections to prevent relative movement.

**7.** A method to assemble a portable drilling rig, the method comprising:

pinning a mast pivot point located at a lower end of a mast structure to an upper pivot point of a pedestal structure, the mast structure being separable from the pedestal structure, and each of the mast structure and pedestal structure are disposed on a rig floor;

pivoting the pedestal structure from a horizontal position to a vertical position about a lower pivot point and securing the pedestal structure to the rig floor;

erecting the mast structure to a vertical position about the upper pivot point of the pedestal structure; and

extending a mast leg from the mast structure to the rig floor and securing the mast structure in the vertical position.

**8.** A method of erecting a drilling rig, the method comprising:

pivoting a pedestal structure about a lower pivot point to a substantially vertical position while an upper pivot point is pinned to a mast pivot point of a mast structure and the mast structure and pedestal structure are disposed on a rig floor, the mast structure being separable from the pedestal structure;

fastening the pedestal structure to an attachment point on the rig floor;

erecting the mast structure above the pedestal structure; and

extending a mast leg from the mast structure to the rig floor and securing the mast structure in a vertical position.

**9.** The method of claim **8**, further comprising latching multiple telescoping mast sections of the mast structure.

**10.** The method of claim **8**, further comprising extending at least one hydraulic cylinder to pivot the pedestal structure.

\* \* \* \* \*