



AUTOLOADER SPECIFICATIONS

Spec	Requirements
FACILITY	
Electrical	120v 60hz 15amp Service Peak amp draw of 12amps, ave operational <5amps
Compressed Air	Requires a minimum incoming air pressure of at least 80psi Min. 2cfm Uses a 1/4" quick connect
Water Pressure	Replaces 8S requirement of: minimum incoming Water pressure of at least 30psi at 10gpm Uses a 1/2" female thread
Operating Mode	Automatic
Labeler Body Dimensions	48.25"w X 27.75" l X 42" h
Labeler Control Dimensions	12"w X 24.25" l X 30" h
Overall with Conveyor	20"w 123.75"l X 32.25"h
Machine Weight	Body = 278 lbs Control = 52 lbs Conveyor =172 lbs



AUTOLOADER SPECIFICATIONS

Spec	Requirements
CONSUMABLES	
Dia. Range	Diameter Range: up to 3.4" Height Range: up to 12"
Material	Glass bottles, aluminum bottles, aluminum cans
PERFORMANCE	
BPH	Stand-alone: Up to 1999 In Series with 8 shooter, paces with the 8S at about a 10% reduction in maximum output to allow for communication between unit

Got Questions? Call us at 1-877-404-8454 for clarifications or to discuss possibilities outside these parameters.